



Gripper	Throat Depth	Flange Height	Working Pressure	Double Sided Grip Force Up To	Actuation Time
PGS10C	.76 [19.3mm]	1.27 [32.3]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10D	.76 [19.3mm]	1.27 [32.3]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10E	.76 [19.3mm]	1.27 [32.3]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10F	.92 [23.4mm]	1.21 [30.6mm]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10R	.75 [19mm]	1.03 [26.3mm]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10S	.76 [19.3mm]	1.27 [32.3]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10T	.76 [19.3mm]	1.27 [32.3]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10U	.76 [19.3mm]	1.27 [32.3]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10V	.76 [19.3mm]	1.27 [32.3]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open
PGS10W	.76 [19.3mm]	1.27 [32.3]	60psi (413kPa) Min. – 100psi (689 kPa) Max.	450lbs (200kgf) @ 80psi (551kPa)	.050±.010 sec close / <.090 sec open